

Teak & Deck Oil



THINNING
0%



COVERAGE
12-16m²/L



APPLICATION
brush,
cloth



DRYING
2 - 3 hours

Special impregnation oil
for hard wood

» PU modified

Kraft Teak & Deck Oil is a polyurethane modified special blend of natural oils, enhanced with wax and UV filters. Ideal for the preservation and freshening of hard or exotic woods such as teak, iroko, bangkirai, oak, mahogany such as niangon & meranti and bare wood. Ideal for garden or terrace furniture, pergolas, fences and wooden boat decks. It fills the pores of the wood in depth, prevents the penetration of water and has great resistance to extreme weather conditions. When used systematically, it nourishes the wood giving it increased resistance to climate change and fading.

Binding Primers A/h (SB).

- VOC Limit Value: 750g/L.
- Maximum content of VOC of the product in its ready to use condition: 590 g/L

» Contains Wax

» High technology UV filters

TECHNICAL DATA

Binder Type	PU /Oil
Density ISO 2811 @ 25°C	0,84 g/mL(±0,02)
Solids Content w/w ISO 3251-03	43%(±3)
Viscosity Flow Cup No4 @ 25°C ISO 2431	13sec (±2)
Coverage per coat	12-16 m ² /L*

* Depending on the absorption and kind of wood

Teak & Deck Oil

Special impregnation oil
for hard wood

SURFACE PREPARATION

The surface must be dry and free of dust, other resin residues or oils. Remove any loose or peeled varnish. Varnished wood must first be cleaned with the paint stripper **Kraft Remover**. The surfaces must be sanded with the appropriate sandpaper (recommended No. 120) to obtain a dull finish. Wet sanding is recommended where possible. Avoid dust generation and exposure to it.

If protection against insects or fungi is required, first apply a layer of **Kraft Wood Care** preservative.

APPLICATION INSTRUCTIONS

- » Wooden surface must be dry. Don't paint in case of rain within 48 hours after the final coat.
- » Do not apply in the sun.
- » Ready to use.
- » Stir well before painting and apply one coat of **Kraft Teak & Deck Oil** along the wood.
- » You can recoat the surface after at least 24 hours.
- » After 5 minutes, when applying the 2nd coat, remove excess material using a dry cloth along the wood.
- » On woods exposed to harsh weather conditions, apply 2 coats of **Kraft Teak & Deck Oil**.
- » If the wood has a very high absorbency, an additional layer may be required up to full saturation.
- » You can apply the material to the surface using a brush or cloth along the wood.
- » Surface drying in 2-3 hours at 25°C and relative humidity 60%. Drying time is affected by weather conditions.
- » The final shade of the wood depends on its original color and age.
- » Avoid application at temperatures lower than 5°C or higher than 35°C and relative humidity greater than 65%.

AFTER USE INSTRUCTIONS

- » Clean the tools thoroughly with **Kraft Brush Solvent**.
- » Close the bucket well to maintain in good condition for future use.
- » For maintenance and freshening, repeat the application once per year.

PACKAGING

It is available in transparent in 0.75L and 2.5L canisters.

HEALTH, SAFETY & ENVIRONMENTAL INFORMATION

Read label before use. For further information please consult the Material Safety Data sheet.

Poison Centre Tel:

+30 210 7793 777

STORAGE

Store the product before and after opening at temperatures between 5°C to 35°C

02/2021 THIS TECHNICAL DATA SHEET SUPERSEDES ALL PREVIOUS EDITIONS RELEVANT TO THIS PRODUCT

2/2

DISCLAIMER: The above technical data, information, recommendations and guidance are based on scientific and technical knowledge, laboratory studies and long experience. However, the above information is considered to be as indicative and should be reviewed in any case in relation to each specific application conditions. Consequently, the suitability of each product in any application must be evaluated after referring to the updated Technical Data Sheet and to the website www.kraftpaints.gr, as well as after contacting the technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable failures after using the product.

DRUCKFARBEN HELLAS S.A.

ASPROPYRGOS 19 300, ATTICA - GREECE | TEL.: +30 210 55 19 500 - FAX: +30 210 55 19 501
www.druckfarben.gr | www.kraftpaints.gr



Toll-free number

800 111 7700 Monday - Friday, 8.00 am - 04.00 pm
 e-mail: paints.orders@druckfarben.gr