

Stone Care

Acrylic stone varnish



It is a high quality solventborne acrylic varnish for stones and porous mineral substrates for exterior and interior use. It protects and decorates porous substrates such as stones, bricks, cementitious substrates etc. Due to its special formula, dries quickly and penetrates deeply into the substrate, providing waterproof and protection from the atmospheric pollutants. It protects its film from mold growth and corrosion caused by the weather conditions. Additionally, it contains UV filters, offering high resistance to sunlight.

- » **High impregnating properties**
- » **Protects the stone from corrosion**
- » **Refreshes the stone appearance**

THINNING
0%



SPREADING RATE
7-8m²/L



TOOLS
brush, roller
or spray-gun



DRY TO TOUCH
1 hour



TECHNICAL DATA

Binder Type	Acrylic
Specific Gravity {ISO2811 @ 25°C}	0.90Kg/L (±0.02)
Solids Content (w/w) {ISO 3251-03}	20% (±2)
Viscosity-Flow Cup N°4 @ 25°C {ISO 2431}	14sec (±2)
Spreading rate per coat*	7-8m ² /L

* Depending on the application conditions and surface absorption.



Binding Primers (A/h), (SB) - ISO 11890-2.

- VOC Limit Value: 750g/L
- Maximum content of VOC of the product in a ready to use condition: 749g/L

Stone Care

Acrylic stone varnish



SURFACE PREPARATION

To ensure good adhesion, the surface must be dry, clean and free of dust, grease, residues, blistered paint or varnish etc.

- » **On new stone surfaces:** Before applying the varnish, wash the surface with water and dry well.
- » **On painted surfaces with mold/algae:** Remove all residues, sand the surface, apply KRAFT MOLD BLOCKER and after 24h remove the mold/algae.
- » **On stone floors:** Remove all residues, wash the surface with water and dry well.

APPLICATION INSTRUCTIONS

- » The product is ready to use.
- » Check the surface moisture before painting. The surface must dry properly.
- » **Tools:** Brush, roller or spray-gun.
- » Stir well before use.
- » Apply 1-2 coats of KRAFT STONE CARE for vertical surfaces and 2 coats for floors.
- » Apply it outdoor or in a well-ventilated area.
- » Minimum recoat time is approx. 4 hours.
- » The surface drying time is approx. 1 hour at 25°C and 50% relative humidity (drying times are longer in wet/cold conditions).
- » Avoid application at temperatures below 10°C or greater than 35°C and relative humidity greater than 50%.

AFTER USE INSTRUCTIONS

- » Close the bucket well to maintain in good condition for future use. Store before and after opening in a cool place and away from sunlight or frost conditions.
- » Clean the tools thoroughly with KRAFT NITRO 1100 and then with water and soap.

PACKAGING

- » Available in transparent in 0.750L and 2.5L containers.

HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Read label before use. For further information please refer to the Material Safety Data Sheet.

Poison Centre Telephone:

+30 210 7793777

STORAGE

- » Store the product before and after opening at temperatures between 5°C to 35°C.

DISCLAIMER: The above technical data, information, recommendations and guidance are based on scientific and technical knowledge, laboratory studies and long experience. However, the above information is considered to be as indicative and should be reviewed in any case in relation to each specific application conditions. Consequently, the suitability of each product in any application must be evaluated after referring to the updated Technical Data Sheet and to the website www.kraftpaints.gr, as well as after contacting the technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable failures after using the product.

DRUCKFARBEN HELLAS S.A.

ASPROPYRGOS 19 300 ATTICA - GREECE | TEL.: +30 210 55 19 500 - FAX: +30 210 55 19 501
www.druckfarben.gr | www.kraftpaints.gr



Toll-free number

800 111 7700 Monday - Friday, 8.00 am - 04.00 pm

Email: paints.orders@druckfarben.gr