



Eco Dur Aqua

Transparent ecological waterbased 100% acrylic primer based on nanotechnology for exterior and interior use



THINNING
50-80%



SPREADING RATE
15-20m²/L



TOOLS
roller, brush
airless
spray-gun



DRY TO TOUCH
1-3 hours



Ecological waterborne primer based on nanotechnology for exterior and interior use. Compared to the conventional primers presents higher alkali resistance, better adhesion and high penetration performance in porous substrates such as plaster-boards, plasters, MDF and cement based surfaces.

It prevents the calcium ions emigration to the topcoat's surface. Virtually odorless, user and environmental friendly, ideal solution for priming children rooms, bedrooms, hospitals and schools.

- » Penetrates into porous substrates
- » Enhanced alkali resistance
- » Reduces the surface absorbance

TECHNICAL DATA

Binder Type	Acrylic
Specific Gravity {ISO 2811 @ 25°C}	1.02Kg/L (±0.02)
Stormer Viscosity {ASTM D 562-05 @ 25°C}	65 KU (±10KU)
Alkali Resistance {ISO 2812-4}	0: No visible alteration after 24h
Spreading Rate*	15-20m ² /L

* Depends on substrate porosity, texture, painting conditions and application method.



Binding primers A/h (W/B).

- Limit value: 30g/L (2010)
- Maximum content of VOC of product in its ready to use condition: 14.9g/L



Eco Dur Aqua

Transparent ecological waterbased 100% acrylic primer based on nanotechnology for exterior and interior use



SURFACE PREPARATION

To ensure proper adhesion and adequate substrate penetration, the surface must be dry, clean and free of dust, oil, salt, rust, loose paint and residues, blistered paint etc. Wet sanding is recommended for the surface preparation.

- » **On new surfaces:** apply one coat of KRAFT ECO DUR AQUA before applying the suitable topcoat of KRAFT
- » **On surfaces that need repairing:** use KRAFT SPACHTEL or KRAFT PUTTY or other suitable repairing material of KRAFT.
- » Allow new plaster or concrete to surfaces to cure a minimum of 30 days prior to primer application.

APPLICATION INSTRUCTIONS

- » The product is not recommended for already painted surfaces.
- » Minimize paint wastage by estimating how much paint you will need.
- » Before you start painting, dilute the primer by adding 50-80% by volume tap water and stir well. 50% v/v dilution is recommended for priming roofs.
- » Appropriate application tools for this product are brush, roller and airless spray gun.
- » Apply one coat of KRAFT ECO DUR AQUA for the best result. Then apply 2 coats of the proper topcoat.
- » **Minimum recoat time:** 4-6 hours.
- » **Surface drying time:** 1-3 hours at 25 °C and 50% relative humidity (drying times are longer in wet / cold conditions).
- » Do not apply at temperatures below 5°C or above 35°C or at humidity levels above 65%.

AFTER USE INSTRUCTIONS

- » Recover unused paint for reuse
- » Close the bucket to maintain in good condition for future use. Store before and after opening in a cool place and away from sunlight or frost conditions.
- » Reuse of paint can effectively minimize the product's life cycle environmental impact.
- » Clean the tools thoroughly with water and soap

PACKAGING

- » Available in 1L, 4L, 18L containers

HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Read label before use. For further information please refer to the Material Safety Data Sheet

Poison Centre Telephone:

+30 210 7793777

STORAGE

- » Store in dry conditions at temperatures between 5°C and 35°C.

DISCLAIMER: The above technical data, information, recommendations and guidance are based on scientific and technical knowledge, laboratory studies and long experience. However, the above information is considered to be as indicative and should be reviewed in any case in relation to each specific application conditions. Consequently, the suitability of each product in any application must be evaluated after referring to the updated Technical Data Sheet and to the website www.kraftpaints.gr, as well as after contacting the technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable failures after using the product.

DRUCKFARBEN HELLAS S.A.

ASPROPYRGOS 19 300 ATTICA - GREECE | TEL.: +30 210 55 19 500 - FAX: +30 210 55 19 501
www.druckfarben.gr | www.kraftpaints.gr



Toll-free number

800 111 7700 Monday - Friday, 8.00 am - 04.00 pm

Email: paints.orders@druckfarben.gr