

Mold Blocker KRAFT

Anti-mold preservative solution

PAINTS



CONSUMPTION

9 - 10m²/L



TOOLS

spray



DRY TIME

24 h



Water-based preservative for building materials used for the maintenance of non-wood building surfaces such as painted or unpainted walls, cement, plaster, joints, tiles, stones etc. by controlling their attack by microbes such as fungus bacteria, algae.

- » Strong action against fungi, bacteria and algae
- » Approved by the Greek Ministry of Rural Development & Food

TECHNICAL CHARACTERISTICS

| | |
|--|------------------|
| Specific Gravity {ISO 2811} @ 25°C | 1.0 kg/L (±0.02) |
| Stormer Viscosity ASTM D {562-05} @ 25°C | 20 - 30 sec |
| pH | 6 - 8 |
| Product Life Cycle | 2 years |



Mold Blocker

Anti-mold preservative solution



SURFACE PREPARATION

- » To remove bacteria and algae mildew, spray KRAFT MOLD BLOCKER on the surface and let it work for about 1 day.
- » Then rub the surface with a sponge or hard brush and rinse the surface with water.
- » Then the surface applied to the KRAFT MOLD BLOCKER is safe for use by humans or animals. To ensure long-lasting protection of the surface in question, apply the material every 4 months.
- » If necessary, after the maintenance, apply 2 coats of KRAFT MASTER HYDROCONTROL above the surface.

PACKAGING

- » It is available in 0.5L containers.

APPLICATION INSTRUCTIONS

- » Application Tools: Spray
- » Dilution: Ready to use
- » Drying time: 20-30 min.
- » Time of action: 24h
- » It shall not be added in primers and topcoats.
- » Applicable throughout the year

STORAGE

- » Protect from direct sunlight and temperatures higher than 45°C or lower than 5°C. Keep it tightly closed.

HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION



Causes severe skin burns and eye damage.
Very toxic to aquatic life.
Toxic to aquatic life with long lasting effects.
Safety data sheet available on request.
Wash hands thoroughly after handling.
Avoid release to the environment.
Wear protective gloves / clothing and eye / face protection.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Immediately call a POISON CENTER or doctor.
If medical advice is needed, have product container or label at hand.
KEEP OUT OF REACH OF CHILDREN
IF SWALLOWED: Immediately call a POISON CENTER or doctor.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Dispose of contents and container to an approved waste disposal plant or recycled in accordance with local / national / international regulations.

Poison Centre Telephone:

+30 210 7793777

| Active Substances (Regulation (EU) No 528/2012) | CAS | g/100g |
|---|------------|--------|
| Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides | 68424-85-1 | 5,00 |

Reg. Number of Authorization PT10-0002

DISCLAIMER: The above technical data, information, recommendations and guidance are based on scientific and technical knowledge, laboratory studies and long experience. However, the above information is considered to be as indicative and should be reviewed in any case in relation to each specific application conditions. Consequently, the suitability of each product in any application must be evaluated after referring to the updated Technical Data Sheet and to the website www.kraftpaints.gr, as well as after contacting the technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable failures after using the product.

DRUCKFARBEN HELLAS S.A.

ASPROPYRGOS 19 300 ATTICA - GREECE | TEL.: +30 210 55 19 500 - FAX: +30 210 55 19 501
www.druckfarben.gr | www.kraftpaints.gr

Toll-free number

800 111 7700 Monday - Friday, 8.00 am - 04.00 pm

Email: paints.orders@druckfarben.gr