

Brush Thinner

High quality brush solvent



It is a high quality solvent mixture of aromatic hydrocarbons for thinning solventborne alkyd single component paints that are applied with brush or roller on wooden or metallic surfaces. It enhances the application properties of the paint and improves the through and surface drying. It is also suitable for degreasing the metallic surfaces before paint application or cleaning the painting tools after use.

- » Alkyd solventborne paints thinner
- » Enhances the application properties
- » Suitable for cleaning the painting tools

TECHNICAL DATA

| | |
|--|---------------|
| Specific Gravity {ASTM D4052 @ 15°C} | 0.77-0.79Kg/L |
| Solubility in water | Insoluble |

Brush Thinner

High quality brush solvent



APPLICATION INSTRUCTIONS

- » Product ready to use.
- » Use it outdoor or in a well-ventilated area.
- » Wear protective gloves, clothing, and eye/face protection equipment.
- » Dilute one component solventborne paints up to specific product indications.
- » Dilute and stir well the mixture before use.
- » Do not use at temperatures below 5°C and above 35°C.

AFTER USE INSTRUCTIONS

- » Close the bucket well to maintain in good condition for future use. Store before and after opening in a cool place and away from sunlight or frost conditions.

PACKAGING

- » It is available in 1L and 4L containers.

HEALTH SAFETY AND ENVIRONMENTAL INFORMATION

Read label before use. For further information please refer to the Material Safety Data Sheet.

Poison Centre Telephone:

+30 210 7793777

STORAGE

- » Store the product before and after opening at temperatures between 5°C to 35°C and relative humidity <50%.

DISCLAIMER: The above technical data, information, recommendations and guidance are based on scientific and technical knowledge, laboratory studies and long experience. However, the above information is considered to be as indicative and should be reviewed in any case in relation to each specific application conditions. Consequently, the suitability of each product in any application must be evaluated after referring to the updated Technical Data Sheet and to the website www.kraftpaints.gr, as well as after contacting the technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable failures after using the product.

DRUCKFARBEN HELLAS S.A.

ASPROPYRGOS 19 300 ATTICA - GREECE | TEL.: +30 210 55 19 500 - FAX: +30 210 55 19 501
www.druckfarben.gr | www.kraftpaints.gr



Toll-free number

800 111 7700 Monday - Friday, 8.00 am - 04.00 pm

Email: paints.orders@druckfarben.gr